



345S
SECURITY SENSOR

**Security Sensor with On/Off
Switchable Encryption.**



2GIG-DW100-345

Indoor Door/Window Contact

The 2GIG® DW100-345 Door/Window sensor is a reliable and versatile sensor designed to protect homes and businesses.

This sensor operates at 345 MHz to communicate with 2GIG security panels, transmitting signals when the magnet is separated from the sensor. It can be installed on doors, windows, and many other objects that open and close. The sensor transmits in non-encrypted mode by default, and can be set to encrypted mode via an on-board switch.



**Stock half as many SKUs
on trucks.**

Easily choose encrypted/
non-encrypted operation
with an internal switch.
2GIG 345S sensors work
for any installation.

**Complete 2GIG security
ecosystem.**

345S sensors work with
the all-new GC Touch,
revolutionary 2GIG EDGE,
and earlier security &
control panels from 2GIG.

GC TOUCH
2GIG EDGE



2GIG products are known for quality and field-proven reliability with more than 5 million security panels and 25 million devices deployed that boast a less than 0.03 percent failure rate – the best in the industry.

2GIG-DW100-345

Indoor Door/Window Contact

345S
SECURITY SENSOR



FEATURES

- Designed for a seamless fit with a included spacer, enabling more door and window applications
- Battery life of up to 8 years, reducing frequent replacement and truck rolls
- Rounded outer with square interior enables accurate installation, for optimized installer experience
- Supports external Normally Open or Normally Closed input
- On/Off switchable encryption

TECHNICAL SPECIFICATIONS

Transmitter Frequency	345MHz
Compatibility	2GIG Security Panels
Code Outputs	Alarm; Alarm Restore; Supervisory; Low Battery; External Alarm; External Restore; Tamper; Tamper Restore
Supervisory Interval	70 Minutes
External Input	Accepts NC or NO dry contact devices
Magnet Type	Rare Earth
Magnet Dimensions (L x W x H)	2.42" x 0.58" x 2.42" (6.1 x 1.47 x 6.1 cm)
Sensor Dimensions (L x W x H)	2.42" x 1.07" x 0.58" (6.1 x 2.7 x 1.47 cm)
Weight	1.24 oz (35 g)
Housing Material	ABS Plastic
Operating Temperature	32°-120° F (0°-49° C)
Relative Humidity	5% to 90%, Non-condensing
Batteries (Installed)	One CR 2450 Lithium Battery
Certification	ETL, FCC, Industry Canada

Specification and availability subject to change without notice.

2GIG 345S sensors offer reliable security coverage for residential and commercial properties to keep clients feeling secure. With sleek, modern designs that seamlessly integrate into any environment, 345S sensors include contact, PIR, glass break, smoke detectors, keyfobs, and more.

2GIG 345S sensors are compatible with the complete 2GIG security ecosystem including the **GC Touch™** and **2GIG EDGE™** security panels.

