

4-Button Keyfob Remote

2GIG-KEY2E-345 (eSeries with encrypted signal)

2GIG-KEY2-345 (non-encrypted signal)



The 2GIG® 4-Button Keyfob Remote communicates with the 2GIG Control Panel on the 345 MHz frequency. It gives users the ability to turn the security system ON and OFF before entering the home or after exiting. If there is an emergency, you can turn on the siren and automatically call the central monitoring station. Keyfobs can be programmed to operate the programmable output in the Control Panel. The keyfob is a lithium coin battery-powered, wireless keyfob designed to fit on a key chain, in a pocket, or in a purse.

SPECIFICATIONS & TECHNOLOGY

Wireless Signal Range	350 ft (106.7 m), open air, with Wireless Control Panel
Code Outputs	Arm; Disarm; Panic; Relay Control
Transmitter Frequency	345.00 MHz (crystal controlled)
Unique ID Codes	Over one (1) million different code combinations
Dimensions (L x W x H)	1.23 x 2.26 x 0.45 in (3.12 x 5.74 x 1.14 cm) typical
Weight (including battery)	0.65 oz (18.4 g)
Housing Material	ABS Plastic
Color	Black
Operating Temperature	32°-120° F (0°-49° C)
Relative Humidity	5-90% Non-condensing
Battery (installed)	One (1) CR 2025 3V or equivalent Lithium coin batteries
Certification	ETL, FCC, and IC