

RIDGE

S-14-100

BATTERY-POWERED WIRELESS DIGITAL KEYPAD

FEATURES

- 100 four-digit access-code capacity
- Wireless range up to 200 feet
- Multiple RF-transmitter options
- Personal master code
- Non-volatile memory
- Variable relay time
- Audible tones



GOES WHERE YOU GO

No wires mean freedom—this device can be located and mounted anywhere you need it.

AS SIMPLE AS IT GETS

From initial install to day-to-day operation, it's all a breeze—no other access control device is as hassle-free and easy to use.

RUGGED & UV-RESISTANT

Constructed from molded, UV-resistant polycarbonate, this keypad will last.

PROGRAMMING YOU KNOW

Quick, simple, and familiar, the programming steps on the keypad are identical to those on all Security Brands, Inc. keypads.

www.ApolloGateOpeners.com | (800) 878-7829 | Sales@ApolloGateOpeners.com...



SPECIFICATIONS

PHYSICAL

Dimensions	5-3/4"(H) x 4-5/8"(W) x 4-1/2"(D)
Shipping Weight	5 lbs.

ELECTRICAL

Input	9 VDC
Current Draw	less than 20 mA @ 12 VDC standby

RELAY

Contact Rating	2 A @ 30 V / .5 A @ 120 V DC Load / AC Load
Max Switching Voltage	125 V / 125 V
Max Carrying Current	2 A / 2 A
Max Switching Power	24 W / 60 VA
Variable Relay Time	1-9 seconds

ENVIRONMENTAL

Operating Temperature	-15 to 175 °F
-----------------------	---------------

AVAILABLE MODELS

WORKS WITH	FREQUENCIES	MODEL
Multi / Digi	300 MHz	S-14-100-300
Nice Apollo	433 MHz	S-14-100-A
US Automatic	433 MHz	S-14-100-U
Multiple Manufacturers	300/310/315/372/390 MHz	S-14-100-375UT
	318 MHz	S-14-100-318